



WEATHER PROOF & RCD ADAPTOR RANGE

Promotional
Prices
Valid Until
December 2007



Weather Proof Switches & Sockets IP66 240v 50Hz (Heavy Duty) Switches 10Amp Colour Box

		Rating	Switch Colour	Body Colour	Approval	Dimensions (mm)	Price £ Each
WS12IP66	1 Gang 2 Way 10Amp IP66 Outdoor Weather Proof Switch 5x20mm Knockouts with Installation Instructions	IP66	Grey	Grey	CE, BS60669	100x100x70	
WS22IP66	1 Gang 2 Way 10Amp IP66 Outdoor Weather Proof Switch 5x20mm Knockouts with Installation Instructions	IP66	Grey	Grey	CE, BS60669	100x100x70	

Sockets 13Amp 3 Pin Colour Box

		Rating	Lid Colour	Body Colour	Approval	Dimensions (mm)	Price £ Each
WSK1IP66	1 Gang 13Amp 3 Pin Unswitched IP66 Outdoor Weather Proof Socket 5x20mm Knockouts with Installation Instructions	IP66	Grey	Grey	CE, BS1363	100x100x75	
WSSK2IP66	2 Gang 13Amp 3 Pin Switched IP66 Outdoor Weather Proof Socket 5x20mm Knockouts with Installation Instructions	IP66	Grey	Grey	CE, BS1363	150x120x75	

Weather Proof Switches & Sockets - IP54 240v 50Hz Weather Proof Outdoor Switches & Sockets - IP54 240v 50Hz with Wiring Instructions

		Rating	Switch Colour	Body Colour	Approval	Dimensions (mm)	Price £ Each
WS12WP	Weather Proof Switch 1 Gang 2 Way 10Amp c/w Through Stepped Gland Individually Boxed	IP54	Black	Grey	CE, TUV-GS	83x58x70	
WS22WP	Weather Proof Switch 2 Gang 2 Way 10Amp c/w Through Stepped Gland Individually Boxed	IP54	Black	Grey	CE, TUV-GS	83x58x70	
WSK1WP	Weather Proof Socket 3 Pin 1 Gang Unswitched - 13Amp c/w Through Stepped Gland Individually Boxed	IP54	Black	Grey	CE, S	83x58x70	
WSK2WP	Weather Proof Socket 3 Pin 2 Gang Unswitched - 13Amp c/w Through Stepped Gland Individually Boxed	IP54	Black	Grey	CE, S	140x83x58	

Safety Box - Multi Function - IP44 "CE" Approved

		Rating		Body Colour	Approval	Dimensions (mm)	Price £ Each
SAFEBOX	6.5-9mm Cable Protection Safety Box c/w Instructions	IP44	-	Green	CE	55Hx60Wx110L	

RCD Sockets 13Amp 3 Pin - 240v 50Hz

		Rating	Fitting	Colour	Approval	Dimensions (mm)	Price £ Each
RCDSK2	13Amp 3 Pin 2 Gang Unswitched RCD Socket Trip Current 30mA, Trip Speed 30mS Clam Pack, Test Facility for Safety Check	IP20	25-35mm	White /Plastic Box	-	142x82x32	
RCDMSSK2	13A 3PIN 2 Gang Unswitched RCD Metal Clad Trip Current - 30mA Trip Time-30ms	IP20	25-35mm	Grey Deep Metal /Plastic Box Clad	CE, BS 7288: 1990	145(L) 90(W) 48(D)	

Guard Master RCD Adaptors 3 Pin 13Amp 30mA-30mS to BS7071

		Rating	Lid Colour	Body Colour	Approval	Dimensions (mm)	Price £ Each
RCDAP1	13Amp 3 Pin 30mS-30mA RCD Adaptor Trip Current 30mA, Trip Speed 30mS	IP20	-	White	BS7071	440x275x165	
RCDPT	13A 3 Pin RCD Plug Top Fused Trip Current - 30mA Trip Time-30ms	IP20	-	White	CE, BS1363 IEC61540	120(L) 60(W) 75(D)	
RCDILC	RCD In Line Connector 16A-240V-50Hz	IP55	-	Black	CE	175(L) 50(W) 50(D)	
RCDSK1WP	13A 3 Pin Single Unswitched Socket Protected by RCD Connected	IP54	-	Grey	BS7288, BS1363	150(L) 45(W) 75(D)	
WRCDSSK2IP66	13Amp Twin Outdoor RCD Socket Weather Proof	IP66	Grey	Grey	CE, BSN B63	150x120x78	

44-48 Freshwater Road, Dagenham, Essex RM8 1RX (England)
Telephone. 020 8503 8500 Facsimile. 020 8503 8900
www.ced-elec.co.uk - info@ced-elec.co.uk

